

Sun 12 XL110 - LED Flood Light

Sun - LED Flood Light Range

Sun 12 XL110 AC
Sun 12 XL110 DC

Sun 24 XL110 AC
Sun 24 XL110 DC

Sun 48 XL110 AC
Sun 48 XL110 DC

Sun 72 XL110 AC
Sun 72 XL110 DC

The **Sun 12 XL110** LED lighting solution is an environmentally friendly, energy saving replacement for a traditional sodium, mercury and halogen style flood light.

This LED flood light is ready for connection to either AC mains power supply or our Mercury solar power management units, which provide a flexible lighting solution where mains power is not available or desired.



These LED flood lights can be used singularly or in groups to provide lighting for applications ranging from recreation area lighting to warehouse lighting, sign lighting, building lighting, car park lighting and perimeter fence lighting.

Note: All LEDs are encased in a compound that will give them protection from any ingress of liquids or solids and all other electronic components are enclosed in an IP66 rated assembly.

Specifications: Sun 12 XL110 - LED Flood Light

	AC	DC
Product Code	S12-A001-D2	S12-D001-B1
Power Consumption LED's	13.68 Watts	
Power Consumption Driver	4.5 Watts	N/A
Total Power Consumption	18.18 Watts	13.68 Watts
Input Voltage	90 – 264Vac	12 VDC
Input Frequency	47 – 63Hz	N/A
Light Source	1.14 W High Power LED	
LED QTY	12	
Total LED Output	1320 lm	
Operating Lumens at 25°C	1056 lm	
LED Colour	Cool White	
Colour Temp (K)	5400 - 6300 degrees K (Standard)	
CRI	Ra>70	
LED Lifespan	50,000 > 80,000 Hours	
Operating Temperature	-30 degrees C to + 50 degrees C	
Working Humidity	0 ~ 95%	
Turn on time	100ns	
Product Size (mm)	210mm x 109mm x 56mm	
Unit colour	Silver	
Net Weight	1.6 Kg	
Mounting	Wall Mounting Bracket (Standard)	
Protection Rate	IP66 (Light Engine & Power Supply)	
Certification	RoHS, CE	
Warranty	3 Years	

Gemma LIGHTING LIMITED

Unit 3 , Marshlands Spur
Farlington
Portsmouth
Hampshire
PO6 1RX

Tel: +44 (0) 844 856 5201
Fax: +44 (0) 844 856 5209

Email: info@gemmalighting.com

